

HomePlug AV (500Mbps) > Ethernet Bridge

The GigaFast HomePlug AV 500Mbps Ethernet Bridge operates on the HomePlug Powerline AV Specification standard, providing up to 500Mbps bandwidth over home AC wiring. PN958-EB2 is one of the smallest HomePlug AV 500Mbps Ethernet Bridge on the market. The PN958-EB2 uses Atheros AR7420 chipset which is optimized for streaming high definition media applications. The AR7420 includes a faster processor, high speed interfaces and an analog front end (AFE). With these added high performance abilities, PN958-EB2 is perfect for ultra-high speed HD entertainment networks in homes and is perfect for areas that are hard to reach by wireless connections. With a plug and play installation, you can easily combine all of your AV electronics together and instantly enjoy your Entertainment Center from virtually any room in your home. Combined with a broadband DSL/Cable connection, every room with electrical power outlets will have easy access to high-speed Internet connection.

Like all of our HomePlug AV products, this PN958-EB2 is equipped with 128-bit AES security encryption. Combining the private home power grid and the 128-bit AES security encryption, this PN958-EB2 is extremely secure compared to other technologies such as WiFi network.



Features

- Qualcomm 7420 chipset
- IEEE1901 / HomePlug AV standard
- Up to 500Mbps PHY rate
- Co-exists with HomePlug 1.0 (14/85mbps)
- Stand-alone unit attaches directly to Broadband device and home power line network for seamless integration
- Security push button for software free configuration
- Power packet utility provides unsophisticated users a way to graphically manage their HomePlug network (optional)

Specifications

Main Chipset	Qualcomm 7420
Computer Interface	IEEE802.3 (10BASE-T)
Standards	IEEE802.3u (100BASE-T)
Network Interface	IEEE 1901 / HomePlug AV
Security	One RJ-45 (10/100Base-T Ethernet)
Data PHY Rate	One 500Mbps power line port supporting co-existence with HomePlug 1.0 (14/85Mbps)
Modulation Schemes	128-bit AES link encryption with key management
Frequency Band	500Mbps over Powerline and 10/100Mbps over Ethernet
Additional Protocols	OFDM symbol modulation on line synchronization
Operation Range	1024/256/64/16/8 - QAM, QPSK, BPSK, ROBO carrier modulation
Cabling	2 ~ 50 Mhz
Operating Temperature	Mix of TDMA and CSMA/CA channel access scheme;
Storage Temperature	CO device generates a periodic beacon carrier for channel access scheme
Humidity	Estimated range of 300 meters in wall power lines
Power Input	Cat. 5 UTP cable
Power Connector	0°C to 40°C ambient temperature
Housing	-20°C to 70°C ambient temperature
Software Utility	10 to 90% maximum (non-condensing)
Status Lights	100 ~ 240V @ 50/60Hz internal
Certifications	Embedded US / EU / UK / AU specifications
	Plastic (64mm x 46.5mm x 24.5mm)
	Device detect/diagnostic, NEK password setup for local and remote device Windows 98 SE, ME, 2000, NT, XP, Vista, or 7 for initial setup (optional)
	Power: on / off
	PLC link: red / orange / green / off
	Ethernet link: solid / blinking / off
	HomePlug AV Powerline certification
	FCC Class B / CE mark

Application

