

HomePlug AV2 (500+Mbps) > Ethernet Bridge

The GigaFast HomePlug AV2 500+Mbps Ethernet Bridge operates on the HomePlug Powerline AV2 Specification standard, providing up to 500+Mbps bandwidth over home AC wiring. PS958-EB5 is one of the smallest HomePlug AV2 500+Mbps Ethernet Bridge on the market. The PS958-EB5 uses Atheros QCA7450 chipset which is optimized for streaming high definition media applications. The QCA7450 includes a faster processor, high speed interfaces and an analog front end (AFE). With these added high performance abilities, PS958-EB5 is perfect for ultra-high speed HD entertainment networks in homes and is perfect for areas that are hard to reach by wireless connections. With a plug and play installation, you can easily combine all of your AV2 electronics together and instantly enjoy your Entertainment Center from virtually any room in your home. Combined with a broadband DSL/Cable connection, every room with electrical power outlets will have easy access to high-speed Internet connection.

Like all of our HomePlug AV2 products, this PS958-EB5 is equipped with 128-bit AES security encryption. Combining the private home power grid and the 128-bit AES security encryption, this PS958-EB5 is extremely secure compared to other technologies such as WiFi network.



Features

- Qualcomm 7450 chipset
- IEEE1901 / HomePlug AV2 standard
- Up to 500+Mbps PHY rate
- Co-exists with HomePlug 1.0 (14/85mbps)
- Stand-alone unit attaches directly to Broadband device and home power line network for seamless integration
- Security push button for software free configuration
- Power packet utility provides unsophisticated users a way to graphically manage their HomePlug network (optional)

Specifications

Main Chipset	Qualcomm 7450
Computer Interface	IEEE802.3 (10BASE-T) IEEE802.3u (100BASE-T) IEEE802.3ab (1000BASE-T)
Standards	IEEE 1901 / HomePlug AV2
Network Interface	One RJ-45 (10/100/1000Base-T Ethernet) One 500+Mbps power line port supporting co-existence with HomePlug 1.0 (14/85Mbps)
Security	128-bit AES link encryption with key management
Data PHY Rate	500+Mbps over Powerline and 10/100/1000Mbps over Ethernet
Modulation Schemes	OFDM symbol modulation on line synchronization 1024/256/64/16/8 - QAM, QPSK, BPSK, ROBO carrier modulation
Frequency Band	2 ~ 68 Mhz
Additional Protocols	Mix of TDMA and CSMA/CA channel access scheme; CO device generates a periodic beacon carrier for channel access scheme
Operation Range	Estimated range of 300 meters in wall power lines
Cabling	Cat. 5 UTP cable
Operating Temperature	0°C to 40°C ambient temperature
Storage Temperature	-20°C to 70°C ambient temperature
Humidity	10 to 90% maximum (non-condensing)
Power Input	100 ~ 240V @ 50/60Hz internal
Power Connector	Embedded US / EU / UK / AU specifications
Housing	Plastic (86mm x 55mm x 27mm)
Software Utility	Device detect/diagnostic, NEK password setup for local and remote device Windows 98 SE, ME, 2000, NT, XP, Vista, or 7 for initial setup (optional) Power: on / off PLC link: red / orange / green / off Ethernet link: solid / blinking / off
Status Lights	
Certifications	HomePlug AV2 Powerline certification FCC Class B / CE mark

Application

